

# Lead Foil Tape - 10 mil NV10LFT

## PRODUCT DESCRIPTION

10 mil lead foil with an electrically conductive acrylic adhesive and release liner.

## PRODUCT CONSTRUCTION

**Substrate** - 10 mil lead foil conforming to ASTM B29 and at a minimum to be 99.5% pure.

**Adhesive** - 3M electrically conductive acrylic adhesive.

## TECHNICAL DATA

### VALUE

### TEST METHOD

Adhesive Thickness (mils)	2 +/- 0.5	VTP-1
Lead Foil Thickness (mils)	10 +/- 0.5	ASTM D1000
Total Thickness (mils) Nominal	12.5	ASTM D1000
Peel Strength (oz./inch) Min -24 hr. dwell	25	ASTM D1000
Resistance through tape (ohms/sq in) max.	20	MIL-STD-202
Volume Resistance (ohm-cm) max.	6.0	VTP-13

*Note: The above are typical values and should **not** be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.*



**Delaware Valley  
Packaging Group**

1425 Wells Drive  
Bensalem, PA 19020  
215-638-8900  
DVPG.com