

Lead Foil Tape - 5 mil NV5LFT

PRODUCT DESCRIPTION

5 mil lead foil with an electrically conductive acrylic adhesive and release liner.

PRODUCT CONSTRUCTION

Substrate - 5 mil lead foil conforming to ASTM B29 and at a minimum to be 99.5% pure.

Adhesive - 3M electrically conductive acrylic adhesive.

TECHNICAL DATA

	VALUE	TEST METHOD
Adhesive Thickness (mils)	2 +/- 0.5	VTP-1
Lead Foil Thickness (mils)	5 +/- 0.5	ASTM D1000
Total Thickness (mils) Nominal	7.5	ASTM D1000
Peel Strength (oz./inch) Min -24 hr. dwell	25	ASTM D1000
Resistance through tape (ohms/sq in) max.	20	MIL-STD-202
Volume Resistance (ohm-cm) max.	6.0	VTP-13

*Note: The above are typical values and should **not** be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.*



**Delaware Valley
Packaging Group**

1425 Wells Drive
Bensalem, PA 19020
215-638-8900
DVPG.com